


## TPC Overview


## ALICE at CERN/LHC




- Dedicated heavy-ion experiment.
- TPC is the central tracking and particle identification detector of ALICE.
- Upgraded for Run3: continuous readout + GEMs.

## Short History of TPC based Experiments


EOS: 1992-1997




ALICE: 2008-now




NA49: 1994-2002




sPHENIX: 2023-2026




STAR: 2000-2026



#### EOS @ BEVALAC






- 1992-1997
- First TPC for heavy ions
- Large acceptance, good PID
- ~2 AGeV fixed target
- $\sim$ 1-10 events/second
- ~1 MB/second data rate
- 15360 pads
- 1.5x1.0 m pad plane
- Mult. limit ~ 200 tracks
- $\sim 10^5$  events in total

## NA49 (NA61) @ SPS


#### North Area 49



- 1994-2002 (NA49)
- Setup of multiple TPCs for tracking and vertexing
- PID for charged particles
- For the first time the energy density for the QGP was reached at the NA-series experiments

#### STAR @ RHIC


#### Solenoidal Tracker At RHIC



- Large TPC for tracking and PID with full azimuthal coverage
- Time-of-flight system
- Calorimetry
- Forward-backward detectors for event plane
- First MAPS based silicon pixel vertexer for HI
- 7.7 GeV 200 GeV + fixed target
- 1 Hz ~4.5 kHz for Au+Au

#### sPHENIX @ RHIC

super PHENIX 2023-2026? (end date depends on EIC start at BNL)



- Full azimuthal coverage,  $|\eta| < 1.1$
- Full calorimetry (EMCAL + HCAL)
- MAPS based vertexer
- TPC with GEM based continuous readout
- ~15 kHz trigger rate
   → > 10 GB/s DAQ
- Focus on hard probes: jets,  $\Upsilon$ , open heavy flavor, photons etc.

# The ALICE TPC

## ALICE TPC Upgrade Timeline




**Start GEM ROC production** 



Start installation FEE and services



**Transportation to LHC P2** 




**Start GEM production** 

Aug 2016 March 2017



**Start GEM ROC installation** 

May 2019




Nov 2019 Sep 2019



Start connection and commissioning

Aug 2020 Dec 2020


## Backside of the TPC




## Insertion of a TPC Sector



## Inside of the TPC




## Central Electrode and Field Cage



Inner part of the field cage


Refection of the padplane. mirrored on the CE Central electrode

Outer part of the field cage



## Voltage Dividers





Spring ring for


connecting to the CE Connections for the water cooling

Water cooled voltage divider


2 on each side (1 inner, 1 outer)


Power dissipation  $\approx 4*8W$  ( $\approx 40min$  to heat the gas by 1K, planned T stability 0.1K)


## TPC is inserted into the L3 Magnet



# More Impressions









## Move Upgraded TPC into the Cave

## Setup in Run 3 (2022-2026)




- ~5000 charged particles per central collision.
- TPC is in between ITS2 and TRD/TOF for tracking.

## The ALICE TPC




- 5 m diameter.
- 5 m length.
- 18 sectors, each subdivided into 4 sections.
- Two sides (A,C) separated by the central electrode (CE).
- Gas mixture: Ne-CO<sub>2</sub>-N<sub>2</sub> (90-10-5).
- Main task: 3D particle track imaging.
- Drift time electrons:  $\sim 100 \,\mu s$ .
- Drift time ions: ~200 ms.
- Interaction rate: ~50 kHz for Pb-Pb, ~500 kHz for p-p but up to ~ 2 MHz for p-p possible.

## 3D Track Imaging



- Charged particle tracks from the collision ionise the gas.
- The electrons are drifting away from the central electrode towards the end caps.
- At the end caps the charge is amplified and measured on the pads  $\rightarrow$  (x,y) information.
- The arrival time  $t_1$  is measured and together with the start time  $t_0$  the z-component can be calculated:  $z = v_D \cdot (t_1 t_0)$ .
- ullet  $v_D$  is the electron drift velocity.

## Momentum Measurement



longitudinal:


$$\tan \theta = \frac{p_T}{p_z}$$


$$ω=q\cdot B/m$$
;  $v_T=ω\cdot r\rightarrow p_T=m$   $v_T=qBr$   
 $p_T[GeV]=0.3Br[T\cdot m]$ 

equation of motion:


$$\vec{F} = q \cdot \vec{v} \times \vec{B} \quad (\vec{B} = B \cdot \vec{e}_z)$$
  
 $\vec{F} = m \cdot \dot{\vec{v}} \rightarrow Helix$ 

## Pb-Pb collision





## Structure of a TPC



05.11.2025

ALICE TPC

#### Gas mixture - Considerations

- Primary ionisation
  - Gas amplification (High voltage) → stability of detector
  - Production of space charge → distortions of the drift field
- Multiple scattering
  - Momentum resolution
- Drift velocity
  - Sensitivity on environment
  - Readout time of the detector
- Diffusion
  - Widening of the signal → two track resolution
  - Signal loss for long drift → signal resolution
  - Gas amplification → detector stability
- Ageing
  - Deterioration of performance over time
  - Risk of breakdown
  - Important is also the choice of ALL materials which are in contact with the gas (outgassing)

#### **ALICE Gas Mixture**

#### Carrier Gas Ne

- Low Z → low multiple scattering → high momentum resolution
- Low primary Ionisation → low space charge → small distortions
- Quench Gas CO<sub>2</sub> (+N<sub>2</sub>)
  - low diffusion → good resolution for long drift
  - No ageing expected → no deterioration of detector performance
  - (quenching of photons with different energies → more stable operation)

#### Disadvantage:


- Very sensitive to gas density changes (drift velocity)
- Large gain (~10<sup>4</sup>) needed → high voltages → might lead to stability problems

# Ionisation, clusters, drifting,...


## Diffusion

E=0 thermal diffusion

$$\langle v \rangle_{\iota} = 0$$



E>0 transport and diffusion





#### Diffusion

The diffusion constant is one of the essential parameters for choosing the gas mixture. To get the desired two track separation and position resolution the diffusion constant has to be chosen very carefully.




How good can you separate two close tracks?





pick-up pads

#### The Pad Plane





- 152 pad rows.
- 552 960 pads in total over 18\*2 sectors.
- 4-6 mm\*7-15 mm pad size.
- Intrinsic resolution of clusters O(< 1 mm).
- Pad plane geometry (pad sizes) fit to the gas mixture and the corresponding diffusion.

#### TPC Clusterizer

Finding peaks per pad row and 3 time bins


Under development: neural network cluster finder






- 10 MHz sampling for clusterization = 100 ns.
- Digits as input (ADC value per pad = dE/dx).
- Creates most of the data in ALICE.
- Done on GPUs during data taking.
- Peak finding in 2D per pad row.

## Tracking



- TPC clusters as input.
- Kalman based particle tracking.
  - $\rightarrow$  curvature of tracks  $\rightarrow$  transverse momentum.

### Run 2 Momentum Resolution



Combined tracking TPC-ITS momentum resolution ~10% at 50 GeV/c

(Pb-Pb at  $\sqrt{s_{NN}} = 2.76$  TeV from 2010).

For latest Run 2 productions, the momentum resolution improved to ~ 5% at 50 GeV/c, as a result of improved TPC-ITS matching.

### Drift of Electrons in an Electric Field

Electrons in a gas drift with a constant drift velocity u<sub>Drift</sub> in an external electric field:

#### **Mechanism**:

Due to its small mass the electron scatters isotropically at the (heavy) gas molecules and looses its initial direction. In between the collisions (mean time between collisions  $\tau$ ) the electrons are accelerated to the velocity  $u_{Drift}$  in the electric Field:

$$u_{Drift} = a \cdot \tau = \frac{F}{m} \cdot \tau = \frac{e}{m} \cdot \tau \cdot E = \mu \cdot E$$

In the next collisions this additional energy is lost, so that there is an equilibrium between the gained energy and the scattering loss; therefore a constant macroscopic drift velocity  $u_{Drift}$  is observed.

### Z-Position: How to Extract the Values

- $\bullet \ z = v_D \cdot (t_1 t_0).$
- Calibration based on matching between ITS and TPC.

$$\Delta z = \underbrace{\left(\frac{v_D^{CCDB}}{v_D^{calib}} - 1\right) \cdot z + \Delta t \cdot v_D^{CCDB} - 250.0 \cdot \left(\frac{v_D^{CCDB}}{v_D^{calib}} - 1\right)}_{\mathbf{m}}$$

$$\mathbf{m}$$

$$\mathbf{B}$$

$$v_D^{calib} = \frac{v_D^{CCDB}}{m+1}$$


$$\Delta t = \frac{b + 250 \cdot \left(\frac{v_D^{CCDB}}{v_D^{calib}}\right)}{v_D^{CCDB}}$$

$$t_0^{used} = t_0^{BC} \cdot LHCbunchSpacingNS \cdot 1E^{-3} + t_0^{CCDB}$$

$$t_0^{calib} = t_0^{used} - \Delta t$$


# TPC Drift Velocity Calibration: Before

• Difference between ITS track and TPC cluster in z before calibration.




# TPC Drift Velocity Calibration: After


• Difference between ITS track and TPC cluster in z after calibration.



# Drift Velocity vs. Time



• Trend follow the inverse pressure except a few outliers.




• t0 almost stable, some dependency on interaction rate.

#### Ionisation

Distinguish between primary and secondary ionisation:

Atoms become excited or suffer primary ionisation, electrons with energies above 100 eV can make secondary ionisation.




Lohse and Witzeling, Instrumentation In High Energy Physics, World Scientific, 1992

$$n_{total} = n_{primary} + n_{secondary} = \frac{\Delta E}{W_i} = \frac{\frac{dE}{dx} \Delta x}{W_i}$$
 $n_{total} \approx 3...4 \cdot n_{primary}$ 

 $W_i$  = mean energy loss per produced ion pair  $\approx 30 \text{ eV}$ 


 $\Delta E$  = total energy loss



#### The Bethe-Bloch Formula

$$\left\langle -\frac{dE}{dx} \right\rangle = Kz^2 \frac{Z}{A} \frac{1}{\beta^2} \left[ \frac{1}{2} \ln \frac{2m_e c^2 \beta^2 \gamma^2 W_{\text{max}}}{I^2} - \beta^2 - \frac{\delta(\beta \gamma)}{2} \right]$$


- dE/dx first falls  $\approx 1/\beta^2$  (kinematic factor)
- a minimum is reached at βγ≈¼
   (Minimum Ionising Particle MIP)
- then again rising due to the In γ2 term (relativistic rise: contributions of more distant particles due to the relativistic expansion of the transverse E-Field)
- at high  $\gamma$  the relativistic rise is cancelled by the "density effect" (fermi plateau: polarisation of medium screens more distant atoms; described by the  $\delta$  parameter)



Minimum Ionising Particle (MIP)

#### Measurement of Ionisation

Example: 1 cm gas counter, filled with Neon;  $n_{prim} \approx 10$  /(cm atm),  $n_{total} \approx 30$ 



≈ 30 Electron-ion-pairs are hard to detect!

Amplifier noise is typically ≈1000 e<sup>-</sup>!

- ⇒ Number of electrons has to be increased noiseless
- ⇒ Gas amplification

# Gas Amplification - Wires


- Development started already in 1948
- Simple concept






$$E = \frac{\lambda}{2\pi\epsilon_0} \frac{1}{r}$$


 If picked up energy between incidents with gas molecules is large enough for ionisation and avalanche starts (distance to wire: r<sub>min</sub>)






## Need for a Quench Gas

- Cross-sections of photon-production is of same order as ionisation
- No influence by electrostatic force of the wire
- · Photons may be energetic enough to make ionisation
- If energy lost outside of  $r_{min}$  (where avalanche starts) self induced ionisation happens  $\rightarrow$  break down of detector
- Process needed to absorb photons inside  $r_{min} \rightarrow$  Quench gas (organic molecule with many degrees of freedom)
  - Examples: CH<sub>4</sub>, C<sub>2</sub>H<sub>6</sub>, ..., CO<sub>2</sub>, CF<sub>4</sub>







# Gas Amplification - GEMs


- Copper coated kapton foils (50µm)
- Holes etched into the foil
- Size ~70µm
- Distance ~140µm


- Apply voltage on copper coating
  - Up to ΔU≈500V
  - Fields up to ~100kV/cm
- Holes act as multiplication channels
- Natural Ion Back-Flow (IBF) suppression





## Readout Chambers: GEMs






- **GEM = Gas Electron Multiplier**
- Stacks of 4 GEM foils
- 3 stacks for the large Outer ReadOut Chambers (OROC)
- 1 stack for the smaller Inner ReadOut Chambers (IROC)

### **GEM Stacks**


- Usually more than 1 GEM foil used (often 3)
- Many advantages
  - Larger gain at lower ΔU → higher stability
  - Allows for higher total gain (cascaded amplification)
  - Large parameter space → tuning of voltages to obtain low IBF




#### GEMs: Ion Backflow

#### Natural IBF suppression:

- Asymmetric mobility [low for ions high for electrons]
  - Electrons move to larger fields in the amplification channel
  - More ions are produced at the edges → trajectory ends on top electrode
- Asymmetric field [drift induction]
  - Many field lines end on top electrode (ion capture)
  - Transfer region allows for good electron extraction







# GEMs: Ion Backflow Optimization


- Challenge: Minimize IBF space charge in drift region!
- Low ion density in drift region requires
  - low primary ionization n<sub>ion</sub>
  - low gain G<sub>eff</sub>
  - low ion backflow IBF

$$n_{tot} = n_{ion} \times IBF \times G_{eff}$$






## **GEM Stacks**



Schematic view of pad plane and 4-GEM stack
GEMs 1 and 4: Standard large-area single-mask GEM foils
GEMs 2 and 3: Large-pitch GEM foils

**Hiahly optimized HV settinas** 




Performance with optimised HV configuration

IBF = Ion BackFlow

 $\sigma$  = energy resolution for  $^{55}$ Fe

# GEMs: Ion Backflow Optimization


- Challenge: Minimize IBF space charge in drift region!
- Goal: IB = 0.5%, at  $G_{eff} = 2000$
- ⇒ Resulting distortions [O(cm)] can be corrected
- Optimisation of IBF:
  - Measurements and simulations
  - Direction of studies: Different gas mixtures, Voltage settings,
     4-GEM configuration



## Gain Calibration


#### Krypton gain calibration


- Well known technique for TPCs
- 83Rb (half life 86 days) decays into 83mKr
- Radioactive 83mKr isotopes decay in TPC volume
- Spectrum for each GEM stack or for each pad
- Stack-by-stack HV adjustment
- Spectrum for each pad → gain calibration (using main peak of spectrum)
- Some remarkable structures
  - foil sagging,
  - wrinkles,
  - GEM hole size distribution



## dE/dx Calibration


- Gain variations expected due to manufacturing tolerances (readout chips, chambers)
- Calibration
  - Release radioactive <sup>83</sup>Kr into the TPC gas
  - Record decay spectrum for each single pad
  - Create gain map on single pad level
  - Repeat ∼ yearly
- Now also done with integrated digital currents.





# Energy loss Measurement

#### Run 3 PID with the GEM-TPC



• Use ADC values of all (up to) 152 clusters.


# Data taking, infrastructure

# **ALICE Computing**



#### 3.6 TBytes/s raw data

- → up to 170 GBytes/s to disk
- 50k CPUs, 2700 GPUs, 130 PBytes disk
- New online/offline system (O<sup>2</sup>)
- Online reconstruction of all events.
- Offline reconstruction with improved calibration.




TDR (O2): CERN-LHCC-2015-006



- pp data:softwareskimming basedon physicstriggers
- Pb-Pb data: all data is kept (minimum bias)

#### TPC data rates in Run 3




#### Dense packed format

~50 kHz Pb-Pb: 800 GBytes/s (CRU - Common Readout Unit)

→still about 20% margin to readout limit

## Auxiliary Systems: Gas System



TPC Gas System at SLXL2

- Recirulating gas system -> recover Ne
- Purifier (removal of H<sub>2</sub>O and O<sub>2</sub>)


05.11.2025 ALICE TPC


# Auxiliary Systems: Cooling

#### Complex cooling system to equalise TPC ter


About 60 adjustable cooling circuits:


- leakless underpressure system
- cooling of ROC bodies
- FEE enveloped in copper plates (≈ 27kW)
- thermal screens towards ITS and TRD
- service Support Wheel closed with copper shields






# Auxiliary Systems: Temperature






About 500 sensors distributed all over the TPC calibrated within ~ 100mK

Successful calibration of the cooling system to design specifications



# Auxiliary Systems: LASER




#### LASERs to measure ExB Effects

- ExB distortions arise from nonparallel E and B fields.
- It is difficult to build a very big detector (~5m) such that E and B fields are always perfectly parallel.
- Remaining effects must be corrected for

in data.

 In ALICE we use a Laser system to calibrate ExB distortions.

#### ExB Effects in Data



- Image shows the y-component (in azimuthal direction) of the space charge distortions at high interaction rates.
- Asymmetry at low radii is due to ExB (from SCD).


#### TPC Readout Electronics


#### SAMPA ASIC

- 130 nm TSMC CMOS
- 32 channels with preamplifier, shaper,
   10 bit ADC and digital filters
- Continuous or triggered readout
- Front-End Cards (FECs)
  - 5 SAMPA chips per FEC (3276 FECs in total)
  - Continuous sampling at 5 MHz
  - All ADC values read out: 3.3 TB/s total
  - Readout link: CERN GBT / Versatile link system
- FPGA-based readout cards receive the data through 6552 optical links










Excellent mean noise: 670 e- @18 pF

# TPC Readout System: O2


- O<sup>2</sup> = Online × offline (the new ALICE data processing cluster)
- 3.5 TB/s continuous raw data flow (all ALICE detectors)
- Continuous data flow is chopped into (sub-)time frames on the FLPs
- Data volume reduction in two steps: On FPGA readout cards and after tracking



66


# Common Mode and Ion Tails


#### Common Mode Effect



- Capacitors in HV distribution often used to reduce CM effect
- But such capacitors would lead to potential problems with discharges
- At high occupancy the CM signals from many tracks will superimpose and lead to a baseline shift
- This baseline shift is measured in the readout system (CRU FPGA) and removed online

### Ion Tail







- 50kHz Pb-Pb, Run3, 2024
- Raw data, with common mode correction activated.
- Circles show reconstructed TPC clusters.
- Every image corresponds to 200 ns.

# TPC Intrinsic Resolution


#### Intrinsic TPC Resolution





- Very low IR p-p  $\rightarrow$  low occupancy  $\rightarrow$  mainly TPC intrinsic effects.
- At low drift length we have a significant fraction of one pad clusters.
- At larger drift length multi-pad clusters dominate.
- Data is in agreement with TDR calculations (modulo known factor  $\sqrt{2}$  due to lower electron transparency).

#### Pb-Pb Space Point Resolution




- Does not depend on IR → no space charge distortion effect!
- Dominated by local occupancy effects.

## Summary

#### **Summary:**


- Space charge distortions are as expected in terms of magnitude and fluctuations.
- Space charge distortion calibration is right now limited by precisions of external detectors.
- TPC intrinsic resolution as expected! Occupancy dependence is dominating the resolution (clusterization + tracking).

# Space Charge Distortion Corrections



## Continuous Readout: Challenges


- Goal: Operate TPC at high luminosity
  - Luminosity for lead collisions: 6×10<sup>27</sup> Hz/cm2
  - Up to 50 kHz interaction rate
  - Up to 5 events overlapping (current gas, shown below)
  - Inspect all minimum bias events
- ⇒ No gating
- ⇒ Continuous readout (no triggers)









- At 50 kHz Pb-Pb about 10.000 ion discs pile up in the TPC
  - → Space charge in the TPC volume created
  - → Distortion of the drifting electron clusters



## Space Charge Distortions


- Ions from the amplification stage move back into the drift volume
- Ions are slow (~200 ms for full drift)
  - Ions from large number of events pile up (~10k events @ 50 kHz IR)
  - Significant space-charge density (SCD) in drift volume
  - Large average distortions (O(5-10 cm))
  - Intrinsic TPC resolution:  $\sim$ 200  $\mu$ m
  - $\rho_{SC} \sim I_{prim} \bullet gain \bullet IBF$







## Extracting the Residuals

- Define reference track position in TPC from ITS extrapolation (or ITS-TRD-TOF interpolation)
- Collect  $\delta y$  and  $\delta z$  differences between distorted clusters and reference points in TPC subvolumes (2.7M voxels)
- Output: *unbinned residuals*
- Build voxel maps from unbinned residuals to extract real distortions  $\Delta X$ ,  $\Delta Y$ ,  $\Delta Z$




## Disentangle the Residuals






- Residuals are always measured at row position.
- The true distortions need to be extracted for each voxel using fits to  $\delta y$  vs tan( $\varphi$ ).

## Crossing Point Method




- Distorted TPC tracks which cross one certain volume element are selected (voxel).
- →The corresponding matched ITS tracks will cross in the respective undistorted frame (every point in the distorted frame has exactly one corresponding point in the undistorted frame basis of SCD correction).
  - The vector between the crossing points in the two frames directly gives the correction.

#### Details of the CPM Method




- For each voxel the ITS tracks are stored as circles nearby the voxel position.
- •Once 10 positive charged or 10 negative charged tracks per voxel are there then crossing points are calculated.
- The circle centres are first shifted by the vector (clustervoxel center) to adjust for the voxel size.
- A running average is calculated per voxel.

## Space Charge Distortion Correction (SCD)




- SCD correction maps correct distortions from ~10 cm down to < 1 mm.</li>
- •Fluctuations are measured and corrected every millisecond.
- We are now close to Run 2 performance in terms of SCD corrections!

## ITS Alignment





## ITS Alignment Status



- •192 staves. All need to be aligned with a precision of about 5 mum.
- Important for SCD maps extraction!


#### Means after ITS alignment






• Means are below 2.5 mum.


#### Width after ITS alignment



•Significant improvement compared to previous alignment.


#### Old vs New Alignment






- New alignment removes the structures from sectors 8 and 17.
- •Overall very smooth map.

#### Correction Workflow




## Space Charge Distortion Maps




- Average maps. Fluctuations and IR dependence are treated on top.
- Distortions up to ~8 cm in radial direction!

#### Splines



- Splines: analytical representation of the binned maps.
- Used during GPU reconstruction.

#### Splines in 2D




• Example of a 2D spline for pad row 100.

#### Interaction Rate Dependence


- In Pb-Pb interaction rate drops rapidly within a fill
  - Additional complication for SCD calibration expected leveling at least for major part of the fill
- SCD correction must account for IR changes


Instantaneous Fill Lumi




#### IR Dependence, Linear Scaling

- $M_{corr}(IR) = (M_{ref}(IR_{ref}) M_{static}) \cdot IR/IR_{ref} + M_{static}$
- $M_{static}$ : long-term-average map at low IR ( $IR \approx 0$ )
- $M_{ref}$ : long-term-average reference map at high IR  $(IR_{ref})$
- Caveat: distortions do not scale exactly linearly with IR









#### IR Dependence, Differential Scaling


- $M_{corr}(IR) = M_{ref}(IR_{ref}) + \Delta M_{ref}^{\pm}/\Delta IR_{ref}^{\pm} \bullet (IR IR_{ref})$
- $M_{ref}$ : long-term-average reference map at high IR  $L_{ref}$
- $\Delta M_{ref}^{\pm}$ : derivative map, difference between two maps at slightly different interaction rates around IR



• IR variations from ZDC or *Integrated Digital Currents* (IDCs)










## Integrated Digital Currents


- *IDCs* the ultimate measure for SC variations and fluctuations:
  - Pad-by-pad ADC values integrated over 1 ms inside the CRU, injected in data stream
- SC density related to IDC via IBF
  - $\rho_{SC} \sim I_{prim} \bullet gain \bullet IBF$
  - $IDC\sim I_{prim} \bullet gain$
- Relevant for  $\rho_{SC}$  fluctuations: *IDC* history over typical *ion drift time* (200ms)









#### Effective Ion Drift Time




- Not all ions from the past 200 ms contribute equally to the distortions
- $\Delta t$  dependent weights developed based on correlation with observed distortions (DCA<sub>r</sub>)
  - Significant improvement compared to flat weight






#### Map Granularity




- Standard setting so far: 36 sectors, 15 bins in Y, 152 in X, 5 in Z: 410400 voxels
- Now: Increase in Z from 5 to 20 (tested up to 25), 20 in Y (tested up to 30)
- Especially at the central electrode we need a higher granularity to follow the gradients.
- Future: Non-equidistant binning!

## 544122, NY=15, NZ=5




- DCA = distance of closest approach to primary vertex.
- 15kHz Pb-Pb
- Standard binning for voxel map
- TPC only tracks!

## 544122, NY=20, NZ=30




- 15kHz Pb-Pb.
- 30 bins in y, 20 bins in z.
- Much better DCAs.

#### Closure Test for Z/X = 1.4 Map



- Typical plots to check the quality of a calibration.
- DCA<sub>R</sub> is flat over full acceptance.


## Closure Test for Z/X = 1.4 Map



- Typical plots to check the quality of a calibration.
- DCA<sub>R</sub> is flat over full acceptance.


## Hardware Related Effects

#### M-Shape Distortions




- In general, very good correspondence between observed distortions and IDCs
  - Ideal tool to correct for SC fluctuations
- Additional M-shaped distortion patterns observed with no correspondence to IDCs
  - Origin is not space charge
  - Magnitude larger than typical SCD
  - Duration O(10s)
  - Only on the A-side
  - Frequency changes but not related to IR
  - Air bubble in the water cooling system cause the effect!
  - Solved now.


#### M-Shape Correction



- M-shaped excursions detected in full data set
- Correction implemented based on parametric model of field cage boundary condition variations
- Added to SCD maps.
- Origin is a leak in one of the field cage resistor rod cooling circuits
- Cooling water removed during YETS solved





#### Sector Edge Fluctuations



- Large spikes from sector edge fluctuations.
- •Only for a few sectors.
- Hardware related effect.
- Special calibration needed.


## Charge up of the Inner Field Cage






- We observe a charge up mainly on the Aside which takes O(10 min).
- No dedicated calibration for this period at the moment.
- To decompose several effects we requested two special calibration runs with various steps in IR at the beginning (charge up) and at the end.


#### Performance K0s






•Significant improvements over time, close to Run2 performance for K0s.


#### D<sup>0</sup> performance





- •Significant improvements over time, also includes new alignment.
- •Still a difference to Run 2 performance.

#### Calibrators within the ALICE TPC







Yongzhen



Pengzhong

- More people are very much welcome.
- Join the ALICE TPC team now!